

KS Series Tool

Part Number	Min. Expansion Range	Max. Expansion Range	Std. Roll Length OAL	Expander Size	Other Roll Length
KS-19	19 in	22 in	42 mm	1";9-11GA	30.50 mm
	0.75 mm	0.87 mm	1.65 in		1.18; 1.97 in
KS-20	20 in	23 in	42 mm	1";13-14GA	30.50 mm
	0.79 mm	0.91 mm	1.65 in		1.18; 1.97 in
KS-22	22 in	25 in	42 mm	1-1/4" ;7GA	30.5 mm
	0.87 mm	0.98 mm	1.65 in		1.18; 1.97 in
KS-23	23 in	26 in	42 mm	1-1/4";9GA	30.5 mm
	0.91 mm	1.02 mm	1.65 in		1.18; 1.97 in
KS-24	24 in	27 in	42 mm	1-1/4";10GA	30.5 mm
	0.94 mm	1.06 mm	1.65 in		1.18; 1.97 in
KS 25	25 in	28 in	42 mm	1-1/4";11-13GA	30.5 mm
	0.98 mm	1.10 mm	1.65 in		1.18; 1.97 in
KS-27	27 in	30 in	42 mm	1-1/4";14-15GA	30.5 mm
	1.06 mm	1.18 mm	1.65 in		1.18; 1.97 in
KS-28	28 in	32 in	42 mm	1-1/4"16GA	30,50,60,70 mm
	1.10 mm	1.26 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-29	29 in	33 in	42 mm	1-1/2"7-1 OGA	30,50,60,70 mm
	1.14 mm	1.30 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-30	30 in	34 in	42 mm	1-1/2"10-12GA	30,50,60,70 mm
	1.18 mm	1.34 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-32	32 in	36 in	42 mm	1-1/2"12-14GA	30,50,60,70 mm
	1.26 mm	1.42 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-35	35 in	41 in	42 mm	1-3/4"8-9GA	50,60,70,80 mm
	1.38 mm	1.61 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-37	37 in	43 in	42 mm	1-3/4"10-12GA	50,60,70,80 mm
	1.46 mm	1.69 mm	1.65 in		1.18; 1.97;2.36; 2.76 in
KS-40	40 in	46 in	50 mm	2"7-9GA	40,60,70,80,90,100 mm
	1.57 mm	1.81 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-42	42 in	48 in	50 mm	2"10-13GA	40,60,70,80,90,100 mm
	1.65 mm	1.89 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-44	44 in	50 in	50 mm	2"12-14GA	40,60,70,80,90,100 mm
	1.73 mm	1.97 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-47	47 in	54 in	50 mm	2"12-14GA	40,60,70,80,90,100 mm
	1.85 mm	2.13 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in

Part Number	Min. Expansion Range	Max. Expansion Range	Std. Roll Length OAL	Expander Size	Other Roll Length
KS-49	49 in	56 in	50 mm	2-1/4" 10-13 GA	40,60,70,80,90,100 mm
	1.93 mm	2.20 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-52	52 in	59 in	50 mm	2-1/4" 14-16 GA	40,60,70,80,90,100 mm
	2.05 mm	2.32 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-54	54 in	62 in	50 mm	2-1/2" 8-13GA	40,60,70,80,90,100 mm
	2.13 mm	2.44 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-57	57 in	66 in	50 mm	2-1/2" 12-16GA	40,60,70,80,90,100 mm
	2.24 mm	2.60 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-60	60 in	69 in	50 mm	2-3/4" 7-11GA	40,60,70,80,90,100 mm
	2.36 mm	2.72 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-65	65 in	74 in	50 mm	3" 7-8GA	40,60,70,80,90,100 mm
	2.56 mm	2.91 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-68	68 in	78 in	50 mm	3-10-14GA	40,60,70,80,90,100 mm
	2.68 mm	3.07 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-72	72 in	82 in	50 mm	3-1/4" 7-11GA	40,60,70,80,90,100 mm
	2.83 mm	3.23 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-77	77 in	87 in	50 mm	3-1/4" 15-16 GA	40,60,70,80,90,100 mm
	3.03 mm	3.43 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-82	82 in	92 in	50 mm	3-1/2" 10-13 GA	40,60,70,80,90,100 mm
	3.23 mm	3.62 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-86	86 in	96 in	50 mm	3-3/4" 8-12 GA	40,60,70,80,90,100 mm
	3.39 mm	3.78 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-90	90 in	102 in	50 mm	4" 9-12GA	40,60,70,80,90,100 mm
	3.54 mm	4.02 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in
KS-96	96 in	108 in	50 mm	4" 16GA	40,60,70,80,90,100 mm
	3.78 mm	4.25 mm	1.97 in		1.57; 2.36; 2.76; 3.15;3.54; 3.94 in