



MODEL NO.	OUTPUT SIZE		"A"	"B"	"C"	"D"	"E"	MAX TORQUE @ 10,000 PSI	INPUT SQ.	WEIGHT
	INCH	MM								
BXT - 2 - D	1-5/8"	41 MM	8.87"	3.23"	.42"	3.60"	1.20"	1588 FT.LBS. 2095 Nm.	3/8"	4 1/2 lbs.
	1-13/16"	46 MM	8.98"							
	2"	50 MM	9.08"							
	2-3/16"	55 MM	9.19"							
BXT - 4 - D	2-3/16"	55 MM	11.84"	4.30"	.56"	4.80"	1.60"	3970 FT.LBS. 5382 Nm.	1/2"	9 3/4 lbs.
	2-3/8"	60 MM	11.94"							
	2-9/16"	65 MM	12.05"							
	2-3/4"	70 MM	12.16"							
BXT - 8 - D	2-3/4"	70 MM	14.81"	5.38"	.70"	6"	2"	7980 FT.LBS. 9694 Nm.	3/4"	19 1/2 lbs.
	2-15/16"	75 MM	14.91"							
	3-1/8"	80 MM	15.02"							
	3-1/2"	90 MM	15.24"							
BXT - 16 - D	3-1/2"	90 MM	17.88"	6.45"	.84"	7.20"	2.40"	13,355 FT.LBS. 16,751 Nm.	1"	31 lbs.
	3-7/8"	100 MM	18.10"							
	4-1/4"	110 MM	18.31"							
	4-5/8"	120 MM	18.53"							
BXT - 32 - D	4-5/8"	120 MM	23.82"	8.60"	1.12"	9.60"	3.20"	31,760 FT.LBS. 39,698 Nm.	1"	70 lbs.
	5"	125 MM	24.04"							
	5-3/8"	130 MM	24.25"							
	5-3/4"	145 MM	24.47"							

NOTE: STATED ACCURACY: +/-6%